

Z300XF-P



H.264+ Digital Video Recorder



Features

- Support AHD, TVI, CVI, CVBS, IP video input
- 8/16CH 5MP/4MP/3MP/1080P recording
- Adopt standard H.264+ high profile compression to get high-quality video at much lower bit rate
- Support VGA maximum 1080P output, HDMI up to 4K output
- Multi-mode recording: manual/timer/motion/sensor
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL Alert
- Cloud services, P2P
- Mobile phone remote monitoring (iOS, Android)
- Multi browser access (IE, Chrome, Firefox, Safari)
- Remote control via IE or CMS : preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- Cloud P2P function
- ONVIF Profile S supported

Rear Panel



Specifications

Model		Z308XF-P	Z316XF-P	
System	Compression	H.264+		
	OS	Embedded Linux		
Video	Input	BNC *8CH	BNC *16CH	
	Record	8CH * 5MP@11fps(AHD); 8CH * 4MP@15fps(AHD); 8CH * 3MP@18fps(AHD); 8CH * 1080P@25fps(AHD/TVI)	16CH * 5MP@11fps(AHD); 16CH * 4MP@15fps(AHD); 16CH * 3MP@18fps(AHD); 16CH * 1080P@25fps(AHD/TVI)	
	Live view	8CH	16CH	
	Playback	4CH	8CH	
	Multi-mode	HD Analog:	8CH*5MP@11fps(AHD); 8CH*4MP@15fps(AHD); 8CH*3MP@18fps(AHD); 8CH*1080P(AHD/TVI)	16CH*5MP@11fps(AHD); 16CH*4MP@15fps(AHD); 16CH*3MP@18fps(AHD); 16CH*1080P(AHD/TVI)
		Hybrid:	4CH*5MP(HD Analog) + 4CH*5MP(IP) 4CH*4MP(HD Analog) + 4CH*4MP(IP)	4CH*5MP(HD Analog) + 4CH*5MP(IP) 4CH*4MP(HD Analog) + 4CH*4MP(IP)
		IP:	4CH*5MP; 8CH*3MP	IP: 8CH*5MP; 16CH*3MP 32CH*2MP
	Encode	VBR/CBR		
	Audio	Audio I/O	8/1	4/1
		Two-way talk	Yes	
Playback	Search mode	Time/Calendar/Event/Channel		
	Functions	Play, pause, FF, FB, digital zoom		
	HDD	2SATA, up to 8TB/bay		
Storage	Network storage	Yes		
	Local	USB drive, External Hard drive		
Backup	Network backup	Yes		
	RJ45	1*10/100Mbps Ethernet port		
Network	Protocol	TCP/IP,DHCP, FTP, DNS, DDNS, NTP, UPNP		
	HDMI	1*HDMI 4K		
Port	VGA	1*VGA		
	RS485	1*RS485 , connect to PTZ or keyboard		
	USB port	3*USB2.0	2*USB2.0	
	Temperature	0 °C ~ + 55 °C		
Others	Humidity	10% ~ 90%		
	Power supply	12V/4A		
	Consumption	<10W (Without HDD)		
	Weight	1.8KG		
	Dimensions	350mm(L)* 296mm(W)* 44mm(H)		